

---

## SECTION 1: IDENTIFICATION

---

**Chemical Name:** Tungsten metal

**Trade name and synonyms:** Wolfram

**Chemical Family:** Refractory Metal (non-ferrous metal)

**Formula:** W

**CAS Number:** 7440-33-7

---

## SECTION 2: HAZARD(S) IDENTIFICATION

---

**Classification:** not considered hazardous material according to Regulation (EC) no. 1272/2008 EC or EC Directive

---

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

---

Material	Percent by Weight	OSHA PEL	ACGIH TLV	ACGIH STEL
Tungsten	> 99%	---	5 mg/m <sub>3</sub>	10 mg/m <sub>3</sub>

---

---

## SECTION 4: First-AID MEASURES

---

**Routes of Exposure:** Dust, mist and/or fumes generated during physical or metallurgical treatment may be inhaled, swallowed or come in contact with skin or eyes.

**Effect of Overexposure:** Dust, mist and fumes generated during physical or metallurgical treatment may cause mild irritation of the nose and throat. With the exception of two Russian studies that found early signs of pulmonary fibrosis in some workers exposed to tungsten trioxide, tungsten metal and tungsten carbide, most studies have shown tungsten to be toxicologically inert. Skin and eye contact may cause irritation due to abrasive action of the dust. Current scientific evidence indicates no adverse effects are likely from accidental ingestion of small amounts of tungsten.

**Emergency and First Aid Procedures:** Applicable for pure tungsten Dust, Mist and Fumes

**Inhalation:** If any symptoms of pulmonary involvement develop, remove from exposure and seek medical attention. Aid breathing if necessary.

**Skin Contact:** If irritation occurs, thoroughly wash affected area with mild soap and water and prevent further contact. If irritation persists, seek medical attention.

**Eye Contact:** If irritation occurs, flush with copious amounts of water for 15 minutes. If irritation persists, seek medical attention.

**Ingestion:** If substantial quantities of dusts are swallowed, give person, if conscious, a large amount of water, induce vomiting and seek medical attention.

Carcinogenic Assessment (NTP annual report, IARC Monographs, other) Tungsten has not been identified as known or suspected carcinogens by NTP, IARC or OSHA.

---

## SECTION 5: FIRE-FIGHTING MEASURES

---

**Flash Point:** NA

**Flammable Limits:** NA

**Extinguishing Media:** Class D. Tungsten Dust (for example, from grinding) may present a moderate fire hazard if allowed to accumulate and exposed to an ignition source. Cover burning material with and inert powder, such as dry sand or limestone, to exclude oxygen. Wrought products do not readily burn.

**Special Fire Fighting Procedures:** For a powder fire confined to a small area, use a respirator approved for toxic dusts and fumes. For a large fire involving this material, firefighters should use self-contained breathing apparatus.

**Unusual Fire and Explosion Hazards:** Dust may present a fire or explosion hazard under favoring conditions of particle size, dispersion, and strong ignition source. When tungsten is heated in air above 750°C, tungsten trioxide sublimates (TLV 5mg/m<sup>3</sup>).

---

## SECTION 6: ACCIDENTAL RELEASE MEASURES

---

**For dust:** Ventilate area of spill. Clean-up using methods which avoid dust generation such as vacuuming (with appropriate filter to prevent airborne dust levels which exceed the TLV or PEL), wet dust mop or wet clean-up. If airborne dust is generated, use an appropriate NIOSH approved respirator.

---

**Phone: 1-800-626-0226 :: 630-325-1001**  
**Fax: 630-325-3571**  
**www.tungsten.com**

**540 Executive Drive**  
**Willowbrook, IL 60527**  
**mts@tungsten.com**

---

## SECTION 7: HANDLING & STORAGE

---

**Precautions To Be Taken In Handling and Storage:** Maintain good housekeeping procedures to prevent accumulation of dust from grinding, etc. Use clean-up methods which minimize dust generation such as vacuuming or wet clean-up.

**Other Precautions:** Mists from wet grinding or cutting may contain tungsten particles; if TLV is exceeded, wear NIOSH approved respirator. Wash hands thoroughly after handling dust, before eating or smoking.

Wash skin exposed to dust at the end of work shift. Do not shake clothing, rags or other items to remove dust. Dust should be removed by washing or vacuuming (with appropriate filters) the clothing, rags, or other items.

NOTE: Reported in EPA TSCA inventory, 1980.

Periodic medical examinations are recommended for individuals regularly exposed to dust.

---

## SECTION 8: EXPOSURE CONTROLS & PERSONAL PROTECTION

---

**Respiratory Protection:** None needed for wrought products. When cutting, heating in air, grinding, etc., use an appropriate NIOSH approved respirator if airborne concentrations exceed the TLV or PEL. All appropriate requirements set forth in 29 CFR 1910.134 should be met.

**Ventilation:** Use local exhaust ventilation which is adequate to limit personal exposure to levels which do not exceed the TLV or PEL. If such equipment is not available, use respirators as specified above. No ventilation is required for wrought products as supplied.

**Protective Gloves:** Gloves are recommended when contact is likely.

**Eye protection:** Safety glasses or goggles are recommended.

**Other protective equipment:** NA

---

Phone: 1-800-626-0226 :: 630-325-1001  
Fax: 630-325-3571  
www.tungsten.com

540 Executive Drive  
Willowbrook, IL 60527  
mts@tungsten.com

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

<b>Melting Point:</b>	3410°C
<b>Vapor Density (Air=1)</b>	NA
<b>Boiling point:</b>	5900°C
<b>Evaporation Rate:</b>	NA
<b>Specific Gravity (H<sub>2</sub>O=1):</b>	19.3
<b>Solubility in Water:</b>	2
<b>Insoluble Vapor Pressure (mm Hg):</b>	NA
<b>Percent Volatile by Volume:</b>	0
<b>Appearance and odor:</b>	Gray metal/no odor

---

## SECTION 10: STABILITY AND REACTIVITY DATA

---

**Stability:** Tungsten is stable.

**Incompatibility (materials to avoid):** Tungsten is very slightly soluble in nitric acid, sulfuric acid, and aqua regia. It is soluble in a mixture of hydrofluoric acid and nitric acid. Avoid oxidizers. Vigorous reaction with bromine trifluoride. Lead oxide mixed with tungsten becomes incandescent upon heating. Tungsten becomes incandescent in cold fluorine. Iodine pentafluoride reacts spontaneously with tungsten with incandescence.

**Hazardous Decomposition Products:** None

**Hazardous Polymerization:** Will not occur

---

Phone: 1-800-626-0226 :: 630-325-1001  
Fax: 630-325-3571  
www.tungsten.com

540 Executive Drive  
Willowbrook, IL 60527  
mts@tungsten.com

---

## **SECTION 11: TOXICOLOGICAL INFORMATION**

---

Classification: No known toxic effects

---

## **SECTION 12: ECOLOGICAL INFORMATION**

---

Classification: No Known ecotoxic effects

---

## **SECTION 13: DISPOSAL INFORMATION**

---

Waste Disposal Method: Dispose of the material following all Federal, State, and Local Regulations. Tungsten scrap, dust, and recovered fume have value.

---

## **SECTION 14: TRANSPORT INFORMATION**

---

**ADR / RID / ADN / IATA (ICAO) / IMDG:** not a dangerous good according to international transport regulations.

---

## **SECTION 15: REGULATORY INFORMATION**

---

**Regulation:** No labeling required. Obey any national or state regulations.

---

Phone: 1-800-626-0226 :: 630-325-1001  
Fax: 630-325-3571  
www.tungsten.com

540 Executive Drive  
Willowbrook, IL 60527  
mts@tungsten.com

---

## **SECTION 16: ADDITIONAL INFORMATION**

---

*Although MIDWEST TUNGSTEN SERVICE, INC. attempts to provide current and accurate information herein, MIDWEST TUNGSTEN SERVICE, INC. makes no representation regarding the accuracy or completeness of the information and assumes no liability for any loss, damage, injury of any kind which may result from or arise out of the use of or reliance on the information by any person. The data contained on this sheet was provided for public display via the internet and is not provided in conjunction with any product sold by MIDWEST TUNGSTEN SERVICE, INC. No warranty of MIDWEST TUNGSTEN SERVICE, INC. products is expressed or implied by this document.*

---

**Phone: 1-800-626-0226 :: 630-325-1001**  
**Fax: 630-325-3571**  
**[www.tungsten.com](http://www.tungsten.com)**

**540 Executive Drive**  
**Willowbrook, IL 60527**  
**[mts@tungsten.com](mailto:mts@tungsten.com)**